




Cosmo

Picture	Code	Nominal Power		Dimensions mm			Working pressure	Weight "Kg"	Connection "in"
		"Kcal/h"	"KW"	Height	Width	Depth			
	CM-30	22720-26163	26.4-30.4	930	453	415	3 bar	113	11/4"
	CM-40	32445-37092	37.7-43.1	930	453	515	3 bar	141	11/4"
	CM-50	42084-47936	48.9-55.7	930	453	615	3 bar	169	11/4"
	CM-60	50346-57231	58.5-66.5	930	453	715	3 bar	197	11/4"
	CM-70	58608-66525	68.1-77.3	930	453	815	3 bar	225	11/4"

Blueline

Picture	Code	Nominal Power		Dimensions mm			Water Content	Weight "Kg"	Connection "in"
		"Kcal/h"	"KW"	Height	Width	Depth			
	BLUELINE 30/3	21700-24000	25.2-27.9	865	500	395	16 L	116	11/4"
	BLUELINE 40/4	30600-34000	35.6-39.5	865	500	495	20 L	146	11/4"
	BLUELINE 50/5	39700-44000	46.2-51.2	865	500	595	24 L	176	11/4"
	BLUELINE 60/6	47900-53000	55.7-61.6	865	500	695	28 L	206	11/4"
	BLUELINE 70/7	55000-61000	64.0-70.9	865	500	795	32 L	238	11/4"

Wall Mounted Boiler

Picture	Code	Nominal Power		Weight "Kg"
		"Kcal/h"	"KW"	
	Xina 1024 S	20400-22000	23.7-25.5	27

Wall Mounted Boiler with Domestic Hot Water Plate Exchanger

Heating and domestic hot water production;

24 kW output fan assisted versions;

Available in natural gas and LPG versions;

Compact dimensions.

Main Characteristics:

Stainless steel burner, complete with ignition electrodes and ionization control probe;

7 L heating expansion vessel;

Primary copper lamellar exchange;

Pump with integrated air purging device;

Domestic hot water stainless steel 12-plate exchanger;

Automatic integrated by-pass.


Multifunctional relay for connection to systems with zone valves or to solar systems or to remote boiler shutdown alarms;

Hydraulic kit for solar integration available (optional);

IPX4D protection degree.


Size: Depth:250mm Width: 400mm Length: 700mm

Wall Mounted Condensing Gaz Boiler With Domestic Hot Water Plate Exchanger

Picture	Code	Nominal Power		Weight "Kg"
		"Kcal/h"	"KW"	
	Xina ECO 1024	20400-21500	23.7-24.9	28.5
	Xina ECO 1028	23000-24000	26.4-27.9	32

Thermopolymer-covered stainless steel heat exchanger;
 Modulation range 1:9
 Modulating gas valve with constant air-to-gas ratio;
 Adjustable maximum heating output;
 Room temperature can be set from the boiler if an external probe is installed;
 Fully pre-mixed burner;
 3-speed pump with integrated air purging device;
 9 L heating expansion vessel;
 12-plate DHW heat exchanger (24 kW);
 14-plate DHW heat exchanger (28 kW);
 Variable-speed combustion fan;
 Microprocessor control board;
 LCD control panel with self-diagnosis function;
 Multifunctional relay for connection to systems with zone valves or to solar systems or to remote boiler shutdown alarms;
 Hydraulic kit for solar integration available (optional).

Floor Standing Gaz Boiler

Picture	Code	Nominal Power		Weight "Kg"
		"Kcal/h"	"KW"	
	Sungaz 27 R	23300-25400	27-29.5	100
	Sungaz 35 R	29800-32700	34.6-38	115

High quality and high thickness EN **GJL200** cast iron heat exchanger and insulation around the body to reduce heat loss and noise. The chimney and the draught diverter, provided with safety control against any return of combustion gas, classify the boiler as "type B11BS".

The Low NOx steel multiflame burner, resistant to high temperatures, is provided with intermittent pilot and ionization flame control.

The front and upper panels have suitable grooves for easy opening.

The electrical, safety, and regulation devices are fitted in the control panel integrated in the casing.

Associated with a remote calorifier through our electric kit (optional).

Heating only and Available in chimney version only